



tesa® 51446

Product Information



Vannoppløselig, enkeltklebende skjøtetape

Produktbeskrivelse

tesa® 51446 er en ensidig resirkulerbar skjøtetape uten innlegg består av flatt papir og et modifisert vannoppløselig akrylklebestoff.

tesa® 51446 viktige egenskaper

- Gode klebeegenskaper
- Kleber godt til bestrøket og ubestrøket papir
- Gode resirkuleringssegenskaper i full pH-område (pH3-pH9)

Farge: Blå, fargeløs

Funksjoner

- Very high tack properties
- High shear strength
- Good adhesion values on coated and uncoated paper
- Good repulpability over full pH-range (pH3 –pH9)

Applikasjon

tesa® 51446 passer spesielt til:

- Skjøting av endestykker
- Generelle bruksområder

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Produktinnhold

- | | | | |
|-----------------|------------------------------|------------------|--------|
| • Bæremateriale | Papir (Glatt) | • Type liner | Ingen |
| • Klebetype | repulpable tackified acrylic | • Total tykkelse | 105 µm |

Egenskaper / ytelsesverdier

- | | | | |
|--------------------------|---------|----------------------------------|--------------|
| • Bruddforlengelse | 2.4 % | • Klebeevne | very good |
| • Bruddstyrke | 77 N/cm | • Lagringstid (emballert) < 25°C | 12 months |
| • Bruddstyrke (på tvers) | 32 N/cm | • Statisk strekkholdkraft | good, medium |

For latest information on this product please visit <http://l.tesa.com/?ip=51446>



tesa[®] 51446

Product Information

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=51446>