



tesa® 64014 Professional



Product Information

tesa® 64014 - tilgjengelig som klar eller brun pakketape - enkel å håndtere, enestående klebestyrke, lukking av middels store kartonger.

Produktbeskrivelse

tesa® 64014 består av et PP-materiale med vannbasert akrylklebestoff.

Den spesielle kombinasjonen garanterer en dempet avrullingsstøy.

tesa® 64014 er meget alders- og lysresistent pga. det vannbaserte akrylklebestoffet. Produktet er klorfritt og kun basert på derivater fra mineraloljer. Derfor er det miljøvennlig å deponere produktet via varmebehandling.

Funksjoner

- The special material combination guarantees a low noise unwinding behaviour.
- Water based acrylic adhesive
- tesa® 64014 has a high age and light resistance.
- The product is chlorine free and based on derivatives of mineral oil only
- The disposal by heat treatment is environmental friendly.

Applikasjon

- Pakking, bunting og lukking
- Forsegling av lette og middels tunge kartonger

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Produktinnhold

- | | | | |
|-----------------|---------|------------------|-------|
| • Bæremateriale | PP-film | • Total tykkelse | 45 µm |
| • Klebetype | Akryl | | |

Egenskaper / ytelsesverdier

- | | | | |
|--------------------|---------|--------------------|----|
| • Bruddforlengelse | 140 % | • Manuel påsetting | Ja |
| • Bruddstyrke | 35 N/cm | | |

Klebekraft

- | | |
|---------------------|----------|
| • Klebeevne på Stål | 2.4 N/cm |
|---------------------|----------|



tesa[®] 64014 Professional

Product Information

Additional Information

tesa[®] 64014 kan brukes med alle manuelle dispensere. For mer praktisk bruk anbefales det at dispenserens friksjon løsnes litt opp. Produktets PV1-versjon kan trykkes på. Tilgjengelige farger: hvit, havannabrun og transparent

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=64014>