



tesa® 51619

Product Information



Tape av PET-fleece til ledningsnett i kupeen

Produktbeskrivelse

tesa® 51619 er en universaltape for kabelfesting i bilkupeen. Den kombinerer viktige egenskaper som støydemping, slitasjemotstand og buntstyrke, samtidig som kabelfestet er fleksibelt, noe som letter bunten ved OEM. tesa® 51619 er optimert til automatisk bruk.

- Støydempende egenskaper
- Slipe-resistent
- Fleksibel og glatt
- Revnebestandig
- Stabil avrullingskraft
- Alder-resistent
- Kraftig klebeevne

Funksjoner

- Noise damping
- Abrasion resistant
- Handtearable

Applikasjon

tesa® 51619 is designed for the passenger compartment, providing flexibility and noise damping. Specifically made for automatic bundling

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Produktinnhold

- | | | | |
|-----------------|--------------|------------------|--------|
| • Bæremateriale | PET-flis | • Total tykkelse | 250 µm |
| • Klebetype | Gummi basert | | |

Egenskaper / ytelsesverdier

- | | | | |
|---------------------------------------|---------------------|-------------------------------|---------|
| • Bruddforlengelse | 20 % | • Lyddempning (LV312) | Class C |
| • Bruddstyrke | 37 N/cm | • Temperature resistance max. | 105 °C |
| • Avrullingskraft (Rull bredde > 9mm) | 4 N/roll (30 m/min) | • Temperature resistance min. | -40 °C |
| • Avrullingskraft (Rull bredde ≤ 9mm) | 4 N/roll (30 m/min) | | |

For latest information on this product please visit <http://l.tesa.com/?ip=51619>



tesa[®] 51619

Product Information

Klebekraft

- Klebeevne på Stål 3 N/cm

Additional Information

Standard widths: 9, 19, 25, 32 mm

Standard lengths: 50 m

- Most combinations of width and length are possible
- Further dimensions are available upon request
- Standard core diameter: 76 mm

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=51619>