



# tesa<sup>®</sup> 4304

## Product Information



Høyt ytende maskeringstape av papir opp til 160 °C

### Produktbeskrivelse

tesa<sup>®</sup> 4304 er en høyt ytende maskeringstape av fint kreppt papir til bruk ved sprøytelakkering. Tapen har lim av naturgummi, er svært temperaturbestandig og kan brukes ved ovntørking opp til 160 °C. Maskeringstapen har god gripeevne og egner seg fremragende til sikker maskering av større områder uten å løsne. Den har lett avrulning, er bestandig overfor løsemidler og kan fjernes uten å etterlate rester.

### Funksjoner

- Smooth and finger freindly paper backing with excellent conformability.
- Recommended for multiple drying cycles
- Secure adherence of paints and fillers to the reverse side avoiding paint flaking.
- High temperature resistance up to 163°C / 325°F covering.

### Applikasjon

- Til krevende maskeringsoppgaver
- Etterlater ikke limrester
- God gripeevne
- Brukes ved spraymaling
- Ovntørking opp til 160 °C

### Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

### Produktinnhold

- |                 |                     |  |        |
|-----------------|---------------------|--|--------|
| • Bæremateriale | Papir (Lett kreppt) | • Total sustainable product excl. liners by weight (acc. EN 16785) | 55 %   |
| • Klebetype     | Naturgummi          | • Total tykkelse   | 145 µm |

### Egenskaper / ytelsesverdier

- |                    |         |                    |           |
|--------------------|---------|--------------------|-----------|
| • Bruddforlengelse | 13 %    | • Hand tearability | very good |
| • Bruddstyrke      | 43 N/cm | • Lett å fjerne    | Ja        |

### Klebekraft

- |                     |        |
|---------------------|--------|
| • Klebeevne på Stål | 4 N/cm |
|---------------------|--------|



# tesa<sup>®</sup> 4304

## Product Information

### Disclaimer

tesa<sup>®</sup> products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa<sup>®</sup> product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=04304>