



tesa[®] 4323

Product Information



Universal Maskeringstape

Produktbeskrivelse

tesa[®] 4323 er en universal maskeringstape som er basert på et fint bæremateriale av kreppt papir og en naturgummikleber. Maskeringstapen er velegnet til allmenne anvendelser, herunder maskering, bunting, forsegling, montering og lett emballering. Bærematerialet av kreppt papir sikrer god formbarhet. Kleberen av naturgummi sikrer god vedheftning på forskjellige overflater samt god gripeevne. Overflatebehandlingen på maskeringstapen forhindrer maleflekker i å renne av tapen, noe som gjør den velegnet til anvendelse i forbindelse med lettere malerarbeid og sprøytemaling.

Sustainable Aspects

57% bio-based content in total product excluding liner (by weight)



For more information: <https://www.tesa.com/product-sustainability>

Funksjoner

- The crepe paper backing ensures a good conformability.
- The natural rubber adhesive system features good adhesion to multiple surfaces as well as a good tack.
- The masking tape offers excellent paint anchorage, making it suitable for light duty spray painting.

Applikasjon

- tesa[®] 4323 brukes i forbindelse med maskering, bunting, forsegling, montering og lett emballering
- Maskeringstapen er ideell til bruk i forbindelse med lettere malerarbeider
- Tapen kan rives av for hånd

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Produktinnhold

- | | | | |
|-----------------|---------------------|--|--------|
| • Bæremateriale | Papir (Lett kreppt) | • Total sustainable product excl. liners by weight (acc. EN 16785) | 57 % |
| • Klebetype | Naturgummi | • Total tykkelse | 125 µm |

For latest information on this product please visit <http://l.tesa.com/?ip=04323>



tesa[®] 4323

Product Information

Egenskaper / ytelsesverdier

- | | | | |
|--------------------|---------|-----------------------------------|-----------|
| • Bruddforlengelse | 10 % | • Hand tearability | very good |
| • Bruddstyrke | 33 N/cm | • Temperaturbestandighet (30 min) | 80 °C |

Klebekraft

- | | |
|---------------------|----------|
| • Klebeevne på Stål | 2.8 N/cm |
|---------------------|----------|

Additional Information

Now also available in black color.

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=04323>