



tesa® 52325

Product Information



Tape til montering av fotopolymerklisjèer

Produktbeskrivelse

tesa® 52310 (transparent), tesa® 52315 (gul), tesa® 52320 (hvit) og tesa® 52325 (rosa) er en serie med tesaprint® platemonteringsløsninger, hver for en spesiell tykkelseskategori.

Avrullingsegenskapene til alle fire tape gir enkel tapefesting. Det pregede PP-innlegget forhindrer dannelse av luftlommer ved montering av plate. Plater kan lett repositioneres under montering, fordi tapens fulle klebeevne først blir effektiv under trykking.

Den høye klebeevnen og gode skjæremotstand til disse tapene, sikrer at det ikke er noe platebevegelse eller kantløftproblemer, selv ved høye hastigheter og lengre trykkeoppgaver. Ved avmontering, vil det ikke være rester på plate eller sylindere.

Funksjoner

- They all feature PVC backings and rubber adhesives and are equipped with a structured PP liner, which prevents the formation of air pockets during plate mounting.
- After printing, the tesaprint® products are easily removable and do not leave residues.

Applikasjon

Feste av fotopolymerplater ved fleksografisk trykking

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Produktinnhold

- | | | | |
|-----------------|------------|--------------|----|
| • Bæremateriale | PVC-film | • Type liner | PP |
| • Klebetype | Naturgummi | | |

Egenskaper / ytelsesverdier

- | | |
|-------------------------|-----|
| • Kategori for tykkelse | 250 |
|-------------------------|-----|



tesa[®] 52325

Product Information

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=52325>