



tesa® 52315

Information Produit



150 µm plate mounting tape

Product Description

tesa® 52310 (transparent), tesa® 52315 (yellow), tesa® 52320 (white) and tesa® 52325 (light pink) are a range of tesaprint® plate mounting tapes, each of a different thickness category.

Since the specially designed adhesive does not reach its final adhesion level immediately, plates can be easily repositioned during plate mounting. Later during printing, the final adhesion has been reached, ensuring secure plate bond and no edge lift.

The tesaprint® products can be used for various applications, e.g. plate mounting on compressible sleeves, letterpress plate mounting, or dry offset blanket mounting.

Caractéristiques

- They all feature PVC backings and rubber adhesives and are equipped with a structured PP liner, which prevents the formation of air pockets during plate mounting.
- After printing, the tesaprint® products are easily removable and do not leave residues.

Application

Plate mounting for various applications

Informations techniques (valeurs moyennes)

Les valeurs dans cette section doivent être considérées comme représentatives ou standards uniquement et ne doivent pas être utilisées à des fins spécifiques.

Product Construction

- | | | | |
|--------------------------|--------------------|----------------------|----|
| • Support | film PVC | • Type de protecteur | PP |
| • Type de masse adhésive | caoutchouc naturel | | |

Propriétés / Valeurs de performance

- | | |
|-------------------------|-----|
| • Catégorie d'épaisseur | 150 |
|-------------------------|-----|



tesa[®] 52315

Information Produit

Disclaimer

Tous les produits tesa[®] sont soumis à des contrôles rigoureux qui garantissent une qualité irréprochable. Toutes les informations et données techniques mentionnées ci-dessus sont données de bonne foi sur la base de notre expérience. Elles sont considérées comme des valeurs moyennes et ne conviennent pas pour une valeur précise destinée à un cahier des charges. C'est pourquoi, tesa SE ne peut donner de garanties expresses ou implicites de qualité marchande ou d'adéquation à un usage particulier. Il est du devoir de l'acheteur (du client) de tester l'adéquation des produits à un usage spécifique par un test approprié. En cas de doute, notre service technique se fera un plaisir de vous venir en aide.



Pour plus d'informations sur ce produit, visitez <http://l.tesa.com/?ip=52315>