



tesa[®] 51194

Information Produit

Product Description

tesa[®] 51194 is a double-sided tape. It consists of a splittable paper backing, modified synthetic rubber adhesive and a PET-film based liner.

Colour: Pink

Caractéristiques

- Special splittable backing leaves no open adhesive residues
- Splitting force especially adjusted to high grammage paper and board
- Very low deviation of the splitting force
- Very good adhesion even on PE- and PP-coated surfaces as well as on board
- High initial tack

Application

tesa[®] 51194 is designed for core starting and end tabbing applications in the paper and liquid board packaging industry. It is especially suitable for PE- and PP-coated surfaces as well as for high grammage paper grades and board.

- Core starting: also compatible with automatic dispensers
- End tabbing: the splittable backing allows (semi-) automatic roll opening

Informations techniques (valeurs moyennes)

Les valeurs dans cette section doivent être considérées comme représentatives ou standards uniquement et ne doivent pas être utilisées à des fins spécifiques.

Product Construction

- | | | | |
|--------------------------|------------------------|----------------------|----------|
| • Support | Papier délamenable | • Type de protecteur | film PET |
| • Type de masse adhésive | caoutchouc synthétique | • Epaisseur totale | 170 µm |

Propriétés / Valeurs de performance

- | | | | |
|----------------|-----------|---------------------------------------|------------|
| • Durée de vie | 12 months | • Résistance au cisaillement statique | bon, moyen |
|----------------|-----------|---------------------------------------|------------|



tesa[®] 51194

Information Produit

Disclaimer

Tous les produits tesa[®] sont soumis à des contrôles rigoureux qui garantissent une qualité irréprochable. Toutes les informations et données techniques mentionnées ci-dessus sont données de bonne foi sur la base de notre expérience. Elles sont considérées comme des valeurs moyennes et ne conviennent pas pour une valeur précise destinée à un cahier des charges. C'est pourquoi, tesa SE ne peut donner de garanties expresses ou implicites de qualité marchande ou d'adéquation à un usage particulier. Il est du devoir de l'acheteur (du client) de tester l'adéquation des produits à un usage spécifique par un test approprié. En cas de doute, notre service technique se fera un plaisir de vous venir en aide.



Pour plus d'informations sur ce produit, visitez <http://l.tesa.com/?ip=51194>