



tesa® Professional 60950

Product Information



Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

• Backing	PVC film coated with mineral particles	• Thickness of liner	180 µm
• Type of adhesive	acrylic	• Thickness of tape	720 µm
• Total thickness	900 µm		

Properties/Performance Values

• Elongation at break	25 %	• Easy to remove	no
• Tensile strength	30 N/cm	• Fluorescent	no
• Batteries included	no	• Hand tearability	good
• Batteries required	no	• Suitable for die cutting	yes
• Chemical Resistance	good		

Adhesion to Values

• Steel	5.8 N/cm
---------	----------

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?mp=60950>