



NOPI® Double-sided tape

Product Information

BNR 56173, 56175, 56174

Product Description

There's always something that needs to be affixed in place, be it a carpet, a picture frame that keeps tilting. The NOPI® Double-Sided Tape is the right choice for indoor fixing, with good adhesion on a variety of surfaces. The synthetic adhesive provides hold for permanent use.

Product Features

- Good adhesion on different variety of surfaces
- Indoor use, room temperature
- Permanent use
- Floor Laying.
- General purpose fixing.

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|--------------------|------------------|-------------------|--------|
| • Type of adhesive | synthetic rubber | • Total thickness | 185 µm |
|--------------------|------------------|-------------------|--------|

Properties/Performance Values

- | | | | |
|-----------------------------|-------------------|--------------------------|--|
| • Adhesive strength | Standard adhesion | • Reusable | no |
| • Applicationfield | Home | • Spare part service | no |
| • Area of use | In- and Outdoor | • Suitable surfaces | Tiles, Most plastics, Glass, Acrylic glass, Cardboard, Plaster, Paper, Metal, Steel, Stone |
| • Batteries included | no | | |
| • Batteries required | no | | |
| • Ecofriendly packaging | no | | |
| • Residue-free removability | no | | |
| | | • Tear resistance | yes |
| | | • Temperature resistance | yes |
| | | • Tensibility | 25 % |



NOPI® Double-sided tape

Product Information

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?cp=NaN>