

# tesapack<sup>®</sup> extra strong

BNR 5049, 5050, 57169, 57170, 57171, 57173, 57249, 58177, 58223

tesapack<sup>®</sup> extra strong is a brown or transparent packaging tape made for demanding applications. It combines a highly tear-proof film with strong adhesion.

## Features

- Highly tear-proof PVC backing
- Natural rubber adhesive ensures high adhesion
- Very good sealing security
- For packaging and bundling of heavy goods
- Even, low-noise unwinding
- Suitable for use in all tesa<sup>®</sup> hand dispensers

## Product Properties

- |                       |                   |                      |           |
|-----------------------|-------------------|----------------------|-----------|
| • Applicationfield    | Office, Home      | • Humidity resistant | yes       |
| • Quality             | Premium quality   | • Solvent free       | no        |
| • Transparency        | High transparency | • Suitable surfaces  | Cardboard |
| • Tear resistant      | yes               | • Reusable           | no        |
| • Writable            | no                | • Refillable         | no        |
| • Hand tearable       | no                | • Shape              | Roll      |
| • Dispenser included  | no                | • Batteries required | no        |
| • Low noise unwinding | yes               | • Batteries included | no        |
| • Spare part service  | no                |                      |           |

## Technical Data

- |                          |                    |                   |       |
|--------------------------|--------------------|-------------------|-------|
| • Residue-free removable | no                 | • Total thickness | 49 µm |
| • Adhesive strength      | Very high adhesion | • Age-resistant   | no    |
| • Type of adhesive       | natural rubber     | • Tensibility     | 75 %  |
| • Backing material       | PVC film           | • Max roll width  | 50 mm |
| • Tensile strength       | 75 N/cm            | • Max roll length | 66    |

# tesapack<sup>®</sup> extra strong

## Disclaimer

tesa<sup>®</sup> products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa<sup>®</sup> product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit  
<http://l.tesa.com/?ip=05049>