

tesa® Powerstrips Ceiling Hook

BNR 58029

Product Features

- Easy to mount without drilling, screws or nails
- Secure hold up to 500g, e.g. mobiles
- Removable without trace thanks to the Powerstrips technology
- Usable on almost all ceilings*
- Revolving hook head enables precise positioning of objects
- Hook reusable with tesa Powerstrips Large
- Completely covered tesa Powerstrips

*Not suitable for use on styrofoam, foamed material, surfaces with non-stick coating, porous materials.

The tesa Powerstrips Ceiling Hook is a self-adhesive, removable and reusable hook designed for the ceiling attachment of any object weighing up to 500g.

Application Fields

- How to apply - Step by step
1. Clean the surface with alcohol or silicone-free glass cleaner
 2. Apply the Powerstrip Large strip on the surface - press for 5 seconds Minimum
 3. Disengage the base plate of the hook and stick it onto the strip - press for 5 seconds Minimum
 4. Let the hook slide down on the base plate until it is locked

Product Construction

- | | | | |
|-----------------|-------|-----------------------|------------------|
| • Hook shape | Round | • Holding power up to | 0.5 Kg |
| • Silicone free | yes | • Type of adhesive | synthetic rubber |

Product Properties/Performance Values

- | | | | |
|---------------------------|--|-------------------------------|--|
| • Applicationfield | Living room,
Children's room,
Office, Hall | • Temperature resistance max. | 35 °C |
| • Humidity resistance | no | • Reusable | yes |
| • UV-resistance | no | • Temperature resistance min. | 5 °C |
| • Reusable with | Powerstrips Large | • Suitable surfaces | Tiles, Glass, Even
wood, Steel, Acrylic
glass, Most plastics |
| • Residue free removal | yes | • Oil- and grease-resistant | no |
| • Waterproof | no | • Hazard material | no |
| • Ozone resistance | yes | • UV-resistant | no |
| • Solvent free | yes | • Material | PS (polystyrol) |
| • Application temperature | 15 °C | | |

tesa® Powerstrips Ceiling Hook

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit
<http://l.tesa.com/?ip=NaN>