

# tesa® Double-Sided Tape Universal

## **Product Information**



185 µm

BNR 56172, 56139, 56170, 56138, 56137, 56171

## **Product Description**

tesa® Double-sided Tape Universal is a highly versatile self-adhesive tape that is ideal for carpet fixation, handicrafts and home decoration.

#### **Product Features**

· Multi-functional: For fixing carpets on different surfaces, for handicrafts and decorating

synthetic rubber

- · Tearable by hand
- · Foil quality

### Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Total thickness

# **Product Construction**

**Properties/Performance Values** 

Type of adhesive

<ul> <li>Adhesive strength</li> </ul>	High adhesion	<ul> <li>Residue-free removability</li> </ul>	no
<ul> <li>Applicationfield</li> </ul>	Home	<ul> <li>Reusable</li> </ul>	no
<ul> <li>Area of use</li> </ul>	Indoor	<ul> <li>Solvent free</li> </ul>	yes
<ul> <li>Batteries included</li> </ul>	no	<ul> <li>Spare part service</li> </ul>	no
<ul> <li>Batteries required</li> </ul>	no	<ul> <li>Suitable surfaces</li> </ul>	Tiles, Brick, Most
<ul> <li>Ecofriendly packaging</li> </ul>	no		plastics, Glass, Acrylic
<ul> <li>Hand tearability</li> </ul>	yes		glass, Cardboard,
<ul> <li>Hazard material</li> </ul>	no		Plaster, Paper, Metal,
<ul> <li>Material</li> </ul>	PP (polypropylene)		Steel, Stone
		<ul> <li>Tear resistance</li> </ul>	yes
		<ul> <li>Temperature resistance</li> </ul>	yes
		<ul> <li>Tensibility</li> </ul>	25 %



# tesa® Double-Sided Tape Universal

**Product Information** 

#### Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.

