



tesapack[®] Paper ecoLogo[®]



Product Information

BNR 05054, 57180, 55337

Product Description

tesapack Paper ecoLogo is an eco-friendly carton sealing tape consisting of 60% bio-based materials. It features a strong backing made from unbleached paper

Product Features

- 60% bio-based packaging tape
- Strong backing made from unbleached paper
- Core made from 100% recycled cardboard
- Contour cuff made from 80% recycled cardboard
- Solvent-free adhesive
- Good sealing security
- Hand-tearable
- Suitable for use with all tesapack[®] hand dispensers

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|--------------------|------------------|-------------------|--------|
| • Backing | Paper | • Total thickness | 107 µm |
| • Type of adhesive | synthetic rubber | | |

Properties/Performance Values

- | | | | |
|--------------------------|---------------|---------------------|-----------|
| • Elongation at break | 3 % | • Material | Paper |
| • Tensile strength | 60 N/cm | • Reusable | no |
| • Adhesive strength | High adhesion | • Solvent free | yes |
| • Ageing resistance (UV) | no | • Suitable surfaces | Cardboard |
| • Applicationfield | Office, Home | • Tear resistance | no |
| • Batteries included | no | • Tensibility | 8 % |
| • Batteries required | no | • Unwind force | 0.6 N/cm |
| • Hand tearability | yes | • Writable | yes |
| • Low noise unwinding | no | | |



tesapack[®] Paper ecoLogo[®]

Product Information

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?cp=NaN>