

tesafilm® transparent

Product Information



BNR 57370, 57378, 57372, 57341, 57371, 57369, 57345, 57340, 04140, 57352, 57405, 57346, 57359, 57404, 57401, 57379, 57406, 57342, 57344, 57402, 57403, 57348, 57356, 57343, 57284

Product Description

tesafilm® transparent is a multi-purpose self-adhesive tape for general office and household use. It combines tear-resistance with strong adhesion.

Product Features

- Transparent
- High tear-resistance
- Strong adhesion
- High age-resistance
- · Silent unwinding
- · PP-foil and solvent-free adhesive

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

•	Backing	BOPP	•	Total thickness	48 μm
•	Type of adhesive	water-based acrylic			

Properties/Performance Values

•	Tensile strength	25 N/cm	•	Residue-free removability	no
•	Adhesive strength	High adhesion	•	Reusable	no
•	Ageing resistance (UV)	yes	•	Roll width max	25 mm
•	Applicationfield	Office, Home	•	Serrated blade	_NULL
•	Batteries included	no	•	Solvent free	yes
•	Batteries required	no	•	Suitable for right and/or left	_NULL
•	Ecofriendly packaging	_NULL		handers	
•	Hand tearability	no	•	Suitable surfaces	Paper, Cardboard
•	Hazard material	no	•	Tear resistance	yes
•	Low noise unwinding	yes	•	Tensibility	48 %
•	Material	PP (polypropylene)	•	Transparency	good
•	Max roll length	66 m	•	Unwind force	2.5 N/cm
•	Photocopy neutral	yes	•	Writable	no



tesafilm® transparent

Product Information

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.

