

tesa® extra Power Removable Repair

Product Information

56431, 4671

Product Description

If you are looking for a tape that sticks reliably and removes cleanly without residue, this cloth tape is the perfect choice. Ideal for all your home projects, from quick fixes to lasting solutions.

Sustainable Aspects

Consisting of 51% renewable materials, such as natural rubber (excluding packaging and core), this tape contributes to sustainability without compromising performance.

Product Features

- Residue-free removal: leaves no adhesive traces
- Strong hold: ideal for repairing, fastening and reinforcing even on rough surfaces
- Easy to use: hand-tearable and writable
- Contributing to sustainability: tape consists of 51% renewable materials, such as natural rubber
- Available in black, white and grey

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|--------------------|----------------|-------------------|--------|
| • Backing | rayon cloth | • Total thickness | 280 µm |
| • Type of adhesive | natural rubber | | |

Properties/Performance Values

- | | | | |
|-----------------------------|---------------|--------------------------|--|
| • Tensile strength | 70 N/cm | • Solvent free | yes |
| • Abrasion resistance | very good | • Suitable surfaces | Acrylic glass, Brick, Cardboard, Glass, Metal, Paper, Plaster, Steel, Stone, Tiles |
| • Adhesive strength | High adhesion | | |
| • Area of use | Indoor | | |
| • Hand tearability | very good | • Tear resistance | yes |
| • Humidity resistance | yes | • Temperature resistance | yes |
| • Residue-free removability | yes | • Tensibility | 9 % |
| | | • Water resistance | yes |
| | | • Writable | yes |

tesa® extra Power Removable Repair

Product Information

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?cp=4671DIYA>