

# tesa<sup>®</sup> Adhesive Nail for Tiles & Metal 2kg



BNR 77762

## Product Features

- For smooth and solid surfaces like tiles indoors
- For objects up to 2kg per nail or 4kg using 2 nails
- Removable without a trace
- Reusable with a new strip

## Product Description

Adhesive Nail for up to 2kg. Perfect for hanging decorative objects and kitchen utensils on smooth and solid surfaces like tiles & metal.

## Application Fields

- How to apply – Step by step
1. To ensure the closest, strongest possible bond, clean the surface with a silicone-free window cleaner or methylated spirit. The surface should be completely dry before application.
  2. The Adhesive Strip should be applied first to the rougher surface.
  3. Press down evenly over the entire strip for at least 5 seconds and then remove the protective foil. Be careful not to touch the exposed adhesive area at any time.
  4. Now apply your tesa<sup>®</sup> Adhesive Nail by aligning it with the top edge of the strip and then folding it down. Press down evenly over the entire nail for at least 5 seconds.
  5. The tab should be left accessible behind your object or beneath the nail for easy removal.

## Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

## Product Construction

- Holding power of strip up to 2 Kg
- Type of adhesive synthetic rubber

# tesa<sup>®</sup> Adhesive Nail for Tiles & Metal 2kg

## Properties/Performance Values

• Chemical resistance	no	• Reusable	yes
• Reusable with	Adhesive Strip 2kg Tiles	• Temperature resistance min.	5 °C
• Residue free removal	yes	• Suitable surfaces	Even wood, Tiles, Acrylic glass, Metal, Steel
• Area of use	Indoor	• Oil and grease resistance	no
• Waterproof	no	• Hazard material	no
• Ozone resistance	no	• UV resistant	no
• Application temperature	15 °C	• Material	PS (polystyrene)
• Temperature resistance max.	35 °C	• Humidity resistance	no

## Disclaimer

tesa<sup>®</sup> products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa<sup>®</sup> product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit  
<http://l.tesa.com/?ip=NaN>