

# tesa<sup>®</sup> Mounting Tape for Wallpaper & Plaster 10kg/m



BNR 77742, 77743

## Product Features

- For textured and sensitive surfaces like wallpaper or plaster indoors
- Holds up to 10kg/m\*
- For permanent applications

\*For optimal results please read instruction leaflet. A max. of 6kg per application/objects is recommended

## Product Description

Mounting Tape for Wallpaper & Plaster holds up to 10kg/m. A permanent way to mount on textured and sensitive surfaces.

## Application Fields

- How to apply – Step by step
1. To ensure the best possible bond, clean the surface of dirt and dust with a dust-free cloth.
  2. Make sure you attach the mounting tape to the rougher surface first. In the case of wallpaper or plaster, this will be the wall. Affix vertical strips that correspond to the entire length of the object. Reinforce the upper portion with shorter strips, since that's where the majority of the weight will be born. Press down firmly across on the entire Mounting Tape surface for at least five seconds.
  3. Remove the protective foil from the tape and position the item on the surface. Take care not to touch the exposed adhesive surface as this could affect the adhesion.
  4. Press firmly on the item for another 5 seconds to ensure an optimal bond with the surface.

## Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

## Product Construction

- |                               |         |                    |                  |
|-------------------------------|---------|--------------------|------------------|
| • Holding power of tape up to | 10 KG/M | • Backing material | PE foam          |
| • Total thickness             | 1350 µm | • Type of adhesive | synthetic rubber |

## Properties/Performance Values

- |                           |       |                               |                    |
|---------------------------|-------|-------------------------------|--------------------|
| • Chemical resistance     | no    | • Temperature resistance max. | 40 °C              |
| • Residue free removal    | no    | • Temperature resistance min. | 10 °C              |
| • Solvent free            | yes   | • Suitable surfaces           | Wallpaper, Plaster |
| • Application temperature | 10 °C | • Humidity resistance         | no                 |

# tesa<sup>®</sup> Mounting Tape for Wallpaper & Plaster 10kg/m

## Disclaimer

tesa<sup>®</sup> products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa<sup>®</sup> product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit  
<http://l.tesa.com/?ip=77742>