



tesa® Adhesive Nail for Tiles & Metal

3kg

BNR 77763

Adhesive Nail for up to 3kg. Perfect for hanging decorative objects and kitchen utensils on smooth and solid surfaces like tiles & metal.

Features

- For smooth and solid surfaces like tiles indoors
- For objects up to 3kg per nail or 6kg using 2 nails
- Removable without a trace
- Reusable with a new strip

Product Properties

• Type of tape	Double-sided adhesive	• Solvent free	yes
• Transparent	no	• Suitable surfaces	Tiles, Glass, Even wood, Steel, Acrylic glass, Most plastics
• UV-resistant	no		
• Water resistant	no	• Reusable	yes
• Humidity resistant	no	• Waterproof	no
• Oil- and grease-resistant	no	• Reusable with	Adhesive Strip 3kg Tiles
• Ozone resistant	no	• Batteries required	no
• Resistance to chemicals	No	• Batteries included	no

Technical Data

• Application temperature	min. 15° C	• Temperature resistance from	5 °C
• Area of use	Indoor	• Temperature resistance up to	35 °C
• Material	PS (polystyrol)	• Silicone free	yes
• Residue-free removable	yes	• Hazard material	no
• Type of adhesive	synthetic rubber		

Application

- How to apply – Step by step
1. For the best possible bond, clean the surface with a silicone-free window cleaner or methylated spirit. The surface should be completely dry before application.
 2. The Adhesive Strip should be applied to the rougher surface.
 3. Press down evenly over the entire strip for at least 5 seconds and only then remove the protective foil. Be careful not to touch the exposed adhesive area at any time.
 4. Now apply your tesa® Adhesive Nail by aligning it with the top edge of the strip and then folding it down. Press down evenly on the entire nail for at least 5 seconds.
 5. The tab should be left accessible behind your object or beneath the nail for easy removal.

tesa[®] Adhesive Nail for Tiles & Metal

3kg

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit
<http://l.tesa.com/?ip=NaN>