



tesa®

Product Information



BNR 40238

Product Description

Il porta asciugamani ad anello tesa® Ekkro da parete, autoadesivo, si monta ovunque efficacemente. Non serve trapano, quindi le superfici restano intatte. Rimovibile in qualsiasi momento senza lasciare traccia e riutilizzabile altrove con un nuovo adattatore BK20. Piace la combinazione di squadratura e curve.

Caratteristiche

- Porta asciugamani ad anello, con tecnologia tesa® Power.Kit (soluzione di montaggio adesiva all-in-one)
- Metallo cromato lucido, squadrato, piastrina quadrata
- Montato sicuro a parete, waterproof, inox garantito
- Utilizzabile su piastrelle, metallo, pietra naturale, marmo, cemento, legno, vetro e molti tipi di plastica
- Non utilizzabile su carta da parati, stucco e superfici con rivestimento antiaderente
- Rimovibile senza residui, riutilizzabile con adattatore BK20
- Facile da applicare senza attrezzi
- Dimensioni del prodotto: 175mm x 195mm x 45mm

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- Type of adhesive Silane modified polymer

Proprietà/Valori di prestazione

- | | | | |
|------------------------|-----------------|--------------------------|-----|
| • Chemical resistance | no | • Riutilizzabile | yes |
| • Humidity resistance | yes | • Privo di solventi | yes |
| • Materiale | Metallo cromato | • Resistente ai raggi UV | yes |
| • Residue free removal | yes | | |



tesa®

Product Information

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?cp=40238>