



tesa® Professional 60100 Fibre Glass



Information Produit

Fibreglass Tape / plasterboard tape

Description produit

tesa® 60100 is a self-adhesive, flat and supple glass fibre tape that is coated with an acrylate adhesive mass. It is highly adhesive and can also be used on rough surfaces. The tear-resistant glass fibre tape provides painters and builders with a professional means of closing gaps in sheetrock panels or holes in walls. After being applied to dry and clean surfaces, a thin layer of putty can be applied and worked in immediately and dries very quickly, saving much time compared to traditional methods.

Application

- Closing gaps in sheetrock panels
- Fixing and patching small holes and cracks

Informations techniques (valeurs moyennes)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Conception du produit

- | | | | |
|--------------------------|----------------|--------------------|--------|
| • Support | fibre de verre | • Epaisseur totale | 260 µm |
| • Type de masse adhésive | acrylique | • Couleur | blanc |

Propriétés / Valeurs de performance

- | | | | |
|----------------------------|-----|---------------------------|----------|
| • Allongement à la rupture | 2 % | • Résistance à la rupture | 102 N/cm |
|----------------------------|-----|---------------------------|----------|

Adhésion aux valeurs

- | | |
|-----------------------------|----------|
| • Pouvoir adhésif sur acier | 0.7 N/cm |
|-----------------------------|----------|



tesa[®] Professional 60100 Fibre Glass

Information Produit

Disclaimer

Tous les produits tesa[®] sont soumis à des contrôles rigoureux qui garantissent une qualité irréprochable. Toutes les informations et données techniques mentionnées ci-dessus sont données de bonne foi sur la base de notre expérience. Elles sont considérées comme des valeurs moyennes et ne conviennent pas pour une valeur précise destinée à un cahier des charges. C'est pourquoi, tesa SE ne peut donner de garanties expresses ou implicites de qualité marchande ou d'adéquation à un usage particulier. Il est du devoir de l'acheteur (du client) de tester l'adéquation des produits à un usage spécifique par un test approprié. En cas de doute, notre service technique se fera un plaisir de vous venir en aide.



Pour plus d'informations sur ce produit, visitez <http://l.tesa.com/?ip=60100>