

52117

Steel Master TP



Information Produit

Plate mounting tape for photopolymer plates in flexographic printing

Description produit

tesa® Softprint 52117 STM TP is a double-coated foam tape, designed specifically for mounting photopolymer plates with a thickness of 1.14mm (0.045") or 1.70mm (0.067") in flexographic label printing.

Caractéristiques

- Foam properties: Highly compressible foam, with superior recovery behavior for excellent print quality. Long lasting recovery characteristic for extended and high speed print runs. Low thickness tolerances for quick print preparation and reduced waste.
- Adhesive properties: High bonding on open side to steel cylinder or sleeve to avoid plate movement. Sufficient bonding to plate to avoid edge lifting or plate movement. Non increasing, controlled bonding power for easy repositioning and especially for easy demounting of thinner plates. Very cohesive adhesive structure for demounting without adhesive residues.
- Additional properties: The structured PP-liner prevents the formation of air pockets when plate mounting. Red color marking indicates the soft foam.
- The soft foam makes this the ideal solution in printing screens and line work.

Application

tesa® Softprint 52117 STM TP is a 380µm (15 mil) category double-coated foam tape, designed specifically for mounting photopolymer plates with a thickness of 1.14mm (0.045") or 1.70mm (0.067") in flexographic label printing.

Informations techniques (valeurs moyennes)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Conception du produit

- | | | | |
|--------------------------|----------------------------|----------------------|--------|
| • Support | Mousse PE avec film laminé | • Type de protecteur | PP |
| • Type de masse adhésive | acrylique à fort tack | • Epaisseur totale | 430 µm |

Propriétés / Valeurs de performance

- | | | | |
|-------------------------|-------|----------|--------|
| • Catégorie d'épaisseur | 380 | • Dureté | souple |
| • Couleur du logo | rouge | | |



52117

Steel Master TP

Information Produit

Disclaimer

Tous les produits tesa® sont soumis à des contrôles rigoureux qui garantissent une qualité irréprochable. Toutes les informations et données techniques mentionnées ci-dessus sont données de bonne foi sur la base de notre expérience. Elles sont considérées comme des valeurs moyennes et ne conviennent pas pour une valeur précise destinée à un cahier des charges. C'est pourquoi, tesa SE ne peut donner de garanties expresses ou implicites de qualité marchande ou d'adéquation à un usage particulier. Il est du devoir de l'acheteur (du client) de tester l'adéquation des produits à un usage spécifique par un test approprié. En cas de doute, notre service technique se fera un plaisir de vous venir en aide.



Pour plus d'informations sur ce produit, visitez <http://l.tesa.com/?ip=52117>