tesa® 4595

Information Produit

High tensile cross filament tape

Description produit

tesa® 4595 is a premium bidirectional filament tape based on polyester filaments laminated to polyester film. tesa® 4595 is tear resistant.
The unique crossweave polyester filament design is different from glass filament which is brittle and tends to break at edges.

Caractéristiques

- High shock resistance
- High conformability to substrates
- Excellent abrasion resistance
- The tape has extremely high longitudinal tensile strength and low elongation.
- The special synthetic rubber adhesive system ensures a secure bond to various surfaces with high tack and high adhesion.

Application

tesa® 4595 is suitable for heavy duty applications, where safety matters:

- Heavy duty bundling
- Heavy duty transport securing
- Fixing
- End-tabbing
- Pipeline and cable wrapping

Informations techniques (valeurs moyennes)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Conception du produit

• Support	fibre PET / film PET	• Epaisseur totale	250 µm
• Type de masse adhésive	caoutchouc synthétique		

Propriétés / Valeurs de performance

• Allongement à la rupture	15 %	• Résistance à la rupture	500 N/cm

Adhésion aux valeurs

• Pouvoir adhésif sur acier	9 N/cm

Pour plus d´informations sur ce produit, visitez http://l.tesa.com/?ip=04595

tesa® 4595

Information Produit

Disclaimer

Tous les produits tesa® sont soumis à des contrôles rigoureux qui garantissent une qualité irréprochable. Toutes les informations et données techniques mentionnées ci-dessus sont données de bonne foi sur la base de notre expérience. Elles sont considérées comme des valeurs moyennes et ne conviennent pas pour une valeur précise destinée à un cahier des charges. C'est pourquoi, tesa SE ne peut donner de garanties expresses ou implicites de qualité marchande ou d'adéquation à un usage particulier. Il est du devoir de l'acheteur (du client) de tester l'adéquation des produits à un usage spécifique par un test approprié. En cas de doute, notre service technique se fera un plaisir de vous venir en aide.

Pour plus d´informations sur ce produit, visitez http://l.tesa.com/?ip=04595