

tesa® EKKRO Spare Toilet Roll Holder, Self-Adhesive, Chromed Metal



Product Information

BNR 40245

Product Description

The self-adhesive tesa® Ekkro spare toilet roll holder is easily mounted on a wall, without drilling. Walls and tiles stay undamaged, and no trace is left behind when the holder is removed. Remounting in another position only requires a new adapter BK20. The holder offers an attractive glossy chrome angular design.

Product Features

- Spare toilet roll holder, with tesa® Power.Kit technology (all-in-one adhesive mounting solution)
- · High gloss chrome-plated metal, angular style, square wall plate
- · Reliable hold, waterproof, guaranteed stainless
- · Works on tiles, metal, natural stone, marble, concrete, wood, glass and many types of plastic
- · Does not work on wallpaper, stucco and other surfaces with non-stick coating
- Can be taken off without a trace and reused with adapter BK20
- · No drilling is needed
- Product dimensions: 50mm x 50mm x 125mm

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

•	Type of adhesive	Silane modified	•	Hook shape	Square
		polymer			

Holding power up to
 6 Kg

Properties/Performance Values

 Applicationfield 	Bathroom	 Residue-free removability 	yes
 Area of use 	Indoor	 Reusable 	yes
 Batteries included 	no	 Reusable with 	Adapter BK20
 Batteries required 	no	 Shape of wall piece 	Rectangular
 Chemical Resistance 	no	 Solvent free 	yes
 Curing time 	12 hour(s)	 Suitable surfaces 	Glazed Tiles, Marble,
 Design series 	tesa® EKKRO		Glass, Metal, Stone,
 Material 	Chromed metal		Concrete, Even wood,
			Most plastics
		 UV resistant 	yes

Waterproof

yes



tesa® EKKRO Spare Toilet Roll Holder, Self-Adhesive, Chromed Metal

Product Information

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.

