

# tesa® extra Power

## **Product Information**



500 μm

### BNR 56064

Supporto

# Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Total thickness

#### **Product Construction**

Proprietà/Valori di prestazione					
• T	ensile strength	33 N/cm	•	Privo di solventi	yes
<ul> <li>A</li> </ul>	desività	Very high adhesion	•	Resistente agli strappi	yes
· A	geing resistance (UV)	yes	•	Temperature resistance	yes
·	land tearability	no	•	Tensione	750 %
	lumidity resistance	yes	•	Resistente ai raggi UV	yes
• R	esistente agli oli e lubrificanti	yes	•	Water resistance	yes
· C	Ozone resistance	yes	•	Resistente all'acqua	yes
• R	esidue free removal	yes	•	Scrivibile	no

Silicone

### Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.

