



# **Product Information**

## BNR 56622, 56623

#### Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

#### **Product Construction**

<ul><li>Supporto</li><li>Type of adhesive</li></ul>	PET cloth natural rubber	Total thickness	420 µm
Proprietà/Valori di prestazione			
Tensile strength	60 N/cm	Privo di solventi	yes
Abrasion resistance	yes	Resistente agli strappi	yes
Adesività	Very high adhesion	<ul> <li>Temperature resistance</li> </ul>	yes
<ul> <li>Ageing resistance (UV)</li> </ul>	yes	<ul> <li>Resistente ai raggi UV</li> </ul>	yes
Resistente agli oli e lubrificanti	yes	Resistente all'acqua	yes
Ozone resistance	yes	Scrivibile	no
Residue free removal	no		

Residue free removal

### Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



Page 1 of 1 – as of 09/02/23 – it-CH