

tesa®

Product Information

BNR 56496, 56497

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

•	Supporto	PE film	•	Total thickness	170 μm
•	Type of adhesive	synthetic rubber			

Proprietà/Valori di prestazione

•	Tensile strength	35 N/cm	•	Residue free removal	no
•	Abrasion resistance	yes	•	Privo di solventi	yes
•	Adesività	Very high adhesion	•	Resistente agli strappi	yes
•	Ageing resistance (UV)	yes	•	Temperature resistance	yes
•	Hand tearability	yes	•	Resistente ai raggi UV	yes
•	Resistente agli oli e lubrificanti	yes	•	Resistente all'acqua	yes
•	Ozone resistance	yes	•	Scrivibile	no

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.

