



Certifications

Our company is focused on international quality, environmental, and occupational safety standards.

Please find more information regarding our certifications at: www.tesa.com/certifications

tesa SE Phone: +49 40 88899 101 tesa.com/company/automotive




Adhesive solutions for electric vehicles

Partner for progress

We play a key role in shaping the future of mobility with innovative and more sustainable product and system solutions. To this end, we are working closely with customers andpartners around the world.

With dedicated development and regional production, we provide industry-leading adhesive tape solutions. Holistic automation and consultancy services enable reliable and efficient production processes.



Enabling passenger safety and design freedom

To make sure every demand is met, we specifically develop self-adhesive tape solutions for e-powertrain applications. It is our business to support you during the entire product development process. We put you and your suppliers first by giving you the individual attention and service you deserve.

Our tapes are suitable for high performance applications inside batteries, such as our solutions for cells, modules, and packs include:

Electrical insulation Reliable protection against short circuits in battery cells and metal parts

Fire protection Providing passenger safety in unlikely thermal runaway and propagation events

Mounting

Next to traditional mounting applications, debonding on demand solutions enable rework, recycle, repair, and reuse of battery components

Venting

Process efficient automated solution for battery packs, providing safety by degassing in case of pressure buildup inside the battery

Sealing

Clean and fast automated application to protect against leakage, water ingress, and corrosion






Accelerating battery production

Tape application is a critical process in the production of electric vehicles as it is used for a variety of purposes, including holding parts in place, providing electrical insulation and advanced tasks like fire protection, venting and sealing.

tesa helps industry partners in finding the right application process and automation partner to accelerate battery projects and increase battery production efficiency. Successful implementation has been proven for all parts of the battery assembly: Cells, modules and packs.



Application for cells

- Electrical insulation
- In-cell applications (electrolyte resistant tapes for jelly roll fixation, stack fixation etc.)
- Anti-thermal propagation (e.g. aerogel encapsulation)

Applications for battery modules

- Mounting
- Metal part insulation
- Thermal management
- Debonding on demand

Applications for battery packs

- Venting
- Box sealing
- Fire protection
- Hole sealing
- Spacing / abrasion protection
- Debonding on demand

Partner up and automate your processes

Discover the cost-effective benefits of tape process - easy handling, no curing time, form stability, and low investment costs.

The tape arrives at your facility in a pre-cured state, meaning that it is already fully functional and can be applied immediately without any need for additional curing time or special equipment. This results in a simpler and more efficient process, as there is no need for heat-up time or the use of safety gloves, making it a convenient and hassle-free solution for your production needs. Another advantage of our tape process is its lack of curing time.



At tesa, we provide the complete solution: from sealing patches, consulting and the application equipment. We aim to improve your processes by offering fully automatic solutions for your application needs. We consult with you to identify the best fitting solution and work with integrators and application suppliers to set up your production line.



Scan this code for further information

Electrical insulation

Area of application

Adhesive tapes with high breakdown voltage guarantee secure electrical insulation for highly automated production processes.

toco colution



Area of application	tesa solution			
Cell wrapping	PET, PCR-PET	Transparent, black, blue	58331, 58353, 58338, 58355, 58352, 58347, 58655	50-110 μm
Metal part insulation	PET, PCR-PET	Transparent, black, blue	58358, 58330, 58351, 58356, 58357, 58344	45-220 μm
In-cell	PET, PP	Blue	58337	35-45 μm

PET: polyethylen terephtalate, PP: polypropylene, PCR: post-consumer-recycled

Fire protection

Area of application

Whether a full solution including functional materials or the ideal adhesive solution: tesa offers products for any substrate, enabling fire protection and matching automotive safety requirements.

tesa solution



Lid protection	Siliconized glass-fibre	White	58311	1200 μm
Fire protection material mounting and encapsulation	PET	Transparent, white	58332, 58334, 58335, 58372,58373, 58374, 58377	50-150 μm
Fireman access	Glassfiber, aluminium, PET	White	54485	9690 µm
Fire- and heat resistant hole covering patches	Aluminium laminated glass-cloth	Silver	54332	1010 µm

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All technical information and data above mentioned are provided to the best of our knowledge on the basis of our practical experience. They shall be considered as average values and are not appropriate for a specification. Therefore tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. The user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.

Mounting

Reliable and strong bonding over the entire vehicle lifetime can be combined with a debonding on demand function, enabling re-manufacturing and recycling.

Area of application	tesa solution			
Battery assembly	PET, non-woven	Transparent	58323, 8853, 58360, 58362, 58363, 58364	50-200 μm
Thermal management	No backing (transfer tapes)	White, transparent	60743, 60744, 58394, 58395, 58398, 58399	30-400 µm
Cell-to-cell /components mounting	PET	Transparent	58360,58362, 58363,58364	50-200 µm

Venting

Reliable emergency degassing which enables automated application, whilst saving weight and space.

Area of application	tesa solution				
Battery pack and module venting	PCR-PET, aluminium Silver, transparent 54112 <400 μm				
Sealing Protection against moistur vehicle lifetime. Box and bo re-opening for service and	attery pack sealing also a				
Area of application	tesa solution				

S

Area of application	tesa solution			
Box and battery pack sealing	Foamed acrylic	Deep black	76730	2800 µm
Hole sealing	Acrylic, PET	Transparent, grey, black	54348, 54336, 54349, 54335	90 μm – 1690 μm



