

tesa® Powerbutton Classic hook Round

Product Information

BNR 59330

Product Description

The tesa® Powerbutton Classic single hook round is a stylish hook for weights up to 6 kg. It is made for damage-free mounting without drilling holes.

Product Features

- · Easy application without drilling, screws or nails
- Extra-strong hold up to 6kg
- Strong hold on most surfaces*
- Usable on and removable from most surfaces**
- Waterproof
- · High temperature resistance
- · Made from stainless steel
- · Do not rust
- · Available as single, double or triple hooks
- Hooks reusable with the tesa® Powerbutton technology

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

• Type of adhesive Silane modified • Hook shape Round

Holding power up to6 Kg

^{*}Does not hold Plaster, Wallpaper, PE, PTFE or PP

^{**}Not removable from Plaster or Wallpaper. Residues might remain



tesa® Powerbutton Classic hook Round

Product Information

Properties/Performance Values

•	Application temperature from	+15 °C	•	Humidity resistance	yes
•	Application temperature to	+30 °C	•	Material	Stainless steel
•	Applicationfield	Bathroom, Kitchen	•	Residue-free removability	yes
•	Area of use	Indoor	•	Reusable	yes
•	Batteries included	no	•	Solvent free	yes
•	Batteries required	no	•	Suitable surfaces	Glazed Tiles, Marble,
•	Chemical Resistance	no			Glass, Metal, Stone,
•	Hazard material	no			Concrete, Even wood,
					Most plastics
			•	UV resistant	yes
			•	Waterproof	no

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.

