

tesa® ESTEETIC Robe Hook, Self-Adhesive, Stainless-Steel

Product Information

BNR 40454

Product Description

A great choice for a space-saving and esthetic place to keep your towels – the tesa® Esteetic robe hook is beautiful. It doesn't cause surface damage. That's because an adhesive solution is used for mounting rather than drilling. You can remove the hook cleanly at any time and reuse it with a new adapter BK20.

Product Features

- Robust robe hook, including the tesa® Power.Kit technology (the all-in-one adhesive mounting solution)
- · Esthetic design, smoothed angular style, stainless-steel look, smoothed square wall plate
- · Safe hold, waterproof, guaranteed stainless
- · Works on tiles, metal, natural stone, marble, concrete, wood, glass and many types of plastic
- · Does not work on wallpaper, stucco and other surfaces with non-stick coating
- · Can be removed without a trace or surface damage. Can be moved elsewhere with adapter BK20
- · Clean, easy application without drilling
- Product dimensions: 50mm x 80mm x 43mm

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

•	Type of adhesive	Silane modified	•	Hook shape	Rounded square
		polymer	•	Special features	Anti fingerprint
•	Holding power up to	6 Kg			

Properties/Performance Values

•	Applicationfield	Bathroom	•	Residue-free removability	yes
•	Area of use	Indoor	•	Reusable	yes
•	Batteries included	no	•	Reusable with	Adapter BK20
•	Batteries required	no	•	Shape of wall piece	Rounded edges
•	Chemical Resistance	no	•	Solvent free	yes
•	Curing time	12 hour(s)	•	Suitable surfaces	Glazed Tiles, Marble,
•	Design series	tesa® ESTEETIC			Glass, Metal, Stone,
•	Material	Metal			Concrete, Even wood,
•	Number of hooks	Double			Most plastics
			•	UV resistant	yes
			•	Waterproof	yes



tesa® ESTEETIC Robe Hook, Self-Adhesive, Stainless-Steel

Product Information

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.

