



# tesa® Masking Tape Perfect

## Product Information

BNR 56532

### Product Description

The tesa® Masking Tape Perfect is a high-quality painters tape made for do-it-yourself wall painting with professional results like perfectly sharp paint edges

### Product Features

- Very tear-proof
- Indoors removable without residues within 14 days
- Suitable for all common paints and varnishes
- Solvent-free
- Consists of 48% renewable primary products

### Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

### Product Construction

- |                    |                |                   |       |
|--------------------|----------------|-------------------|-------|
| • Backing          | Paper          | • Total thickness | 95 µm |
| • Type of adhesive | natural rubber |                   |       |

### Properties/Performance Values

- |                             |                 |                                   |         |
|-----------------------------|-----------------|-----------------------------------|---------|
| • Applicationfield          | Home            | • Residue-free removable after... | 14 days |
| • Area of use               | In- and Outdoor | • days                            |         |
| • Batteries included        | no              | • Reusable                        | no      |
| • Batteries required        | no              | • Solvent free                    | yes     |
| • Ecofriendly packaging     | yes             | • Spare part service              | no      |
| • Hand tearability          | yes             | • Tear resistance                 | yes     |
| • Hazard material           | no              | • UV resistant                    | yes     |
| • Residue-free removability | yes             | • Writable                        | yes     |



# tesa® Masking Tape Perfect

## Product Information

### Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?cp=NaN>