

# tesa® Powerstrips Waterproof Small

**Product Information** 



BNR 59778

#### **Product Features**

- Strong hold for objects on surfaces like tiles, glass, etc.\*
- Removable without a trace due to the Powerstrips Waterproof technology
- Maximum hold of up to 1kg on smooth surfaces
- Especially developed to fix objects in wet areas (e.g. shower, bathtub, etc.)
- Suitable for the Powerstrips Waterproof Small hooks

\*Not suitable for use on styrofoam, foamed material, surfaces with non-stick coating, porous material

### **Application Fields**

How to apply:

1. Clean the surface with alcohol or silicone-free glass cleaner

2. Take the included waterproof primer tissue and wipe over the surface for bonding preperation - wait for 10 seconds minimum

- 3. Apply the Powerstrip Waterproof Small strip on the object press for 5 seconds minimum
- 4. Fix object onto surface press for 5 seconds minimum
- 5. Make sure the tab can be accessed for removal

#### Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

### **Product Construction**

- Type of adhesiveTotal thickness
- synthetic rubber 650 μm

1Kg

Holding power up to 1 Kg
Hook shape \_NULL

Holding power of strip up to

Page 1 of 2 – as of 14/03/24 – en-US



# tesa® Powerstrips Waterproof Small

**Product Information** 

### **Properties/Performance Values**

•	Ageing resistance (UV)	yes
٠	Application temperature from	-15 °C
٠	Applicationfield	Bathroom, Kitchen
•	Area of use	Indoor
٠	Batteries included	no
٠	Batteries required	no
٠	Chemical Resistance	no
٠	Hazard material	yes
٠	Humidity resistance	yes
•	Material	_NULL
٠	Oil and grease resistance	no

<ul> <li>Ozone resistance</li> <li>Residue-free removability</li> <li>Reusable</li> <li>Reusable with</li> <li>Solvent free</li> <li>Suitable surfaces</li> </ul>	yes yes no _NULL no Even wood, Tiles, Most plastics, Glass, Acrylic glass, Steel, Metal
• Temperature resistance max.	35 °C
• Temperature resistance min.	5 °C
UV resistant	no
Water resistance	yes
<ul> <li>Waterproof</li> </ul>	yes

### Disclaimer

tesa<sup>®</sup> products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa<sup>®</sup> product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.

