

# tesa® Powerstrips Self-Adhesive Hook L Metal Oval



## **Product Information**

BNR 58261

#### **Product Features**

- · Easy to mount without drilling, screws or nails
- · Strong hold up to 2 kg
- Removable without a trace thanks to the Powerstrips technology
- · High quality design, brushed stainless steel
- Usable on tiles, glass, wood, plastic and a variety of other smooth surfaces\*
- · Hooks reusable with tesa Powerstrips Large

## **Application Fields**

How to apply - Step by step:

- 1. Clean the surface with alcohol or silicone-free glass cleaner
- 2. Apply the Powerstrip Large strip on the surface press for 5 seconds minimum
- 3. Disengage the base plate of the hook and stick it onto the strip press for 5 seconds minimum
- 4. Let the hook slide down on the base plate until it is locked

## Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

#### **Product Construction**

•	Type of adhesive	synthetic rubber	•	Hook shape	Oval
•	Holding power up to	2 Kg	•	Silicone free	yes

<sup>\*</sup>Not suitable for use on styrofoam, foamed material, surfaces with non-stick coating, porous material



## tesa® Powerstrips Self-Adhesive Hook L Metal Oval

## **Product Information**

## **Properties/Performance Values**

<ul> <li>Application temperature from</li> <li>Application temperature to</li> <li>Applicationfield</li> <li>Area of use</li> <li>Batteries included</li> <li>Batteries required</li> <li>Chemical Resistance</li> <li>Hazard material</li> <li>Humidity resistance</li> </ul>	+15 °C +35 °C Bathroom, Kitchen Indoor no no no	<ul> <li>Ozone resistance</li> <li>Residue-free removability</li> <li>Reusable</li> <li>Reusable with</li> <li>Solvent free</li> <li>Suitable surfaces</li> </ul>	no yes yes Powerstrips Large yes Glazed Tiles, Glass, Even wood, Steel, Acrylic glass, Most plastics, Metal
<ul><li>Material</li><li>Oil and grease resistance</li></ul>	Stainless steel no	<ul><li>Temperature resistance</li><li>Temperature resistance max.</li></ul>	yes 35 ℃
		<ul><li>Temperature resistance min.</li><li>UV resistant</li><li>Waterproof</li></ul>	15 °C no no

### Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.

