

# tesa® Adhesive Screw Triangular for Brick & Stone 5kg



## Product Information

BNR 77904

## Product Description

Adhesive screw for up to 5kg. Ideal for mounting objects with corner holes on rough and solid surfaces like brick and stone.

## Product Features

- For rough and solid surfaces like brick & stone
- Holds up to 5kg per screw or 10kg using 2 screws
- Alignable to invisibly hide behind the object
- Removable from firm surfaces
- Suitable for indoor and outdoor use

## Application Fields

How to apply – Step by step1. Use a brush to get rid of as much grit or dust as you can from the surface to secure an optimal bond.

2. Peel off the protective foil from the adhesive foam tape and lightly press the adhesive screw to the surface. The foam tape is only used to keep the screw in place while you apply the adhesive. Make sure the screw head is aligned so that the body of the Adhesive Screw will be hidden behind your object.

3. Pierce the nozzle on the tube of adhesive and pop the key over the other end.

4. Squeeze the adhesive into the bigger hole in the screw body by giving the key a twist. Continue until the adhesive begins to come out of the smaller hole and the cavity is filled evenly. Allow 12 hours for the adhesive to dry before you put weight on it.

## Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

## Product Construction

- |                    |                         |                                |      |
|--------------------|-------------------------|--------------------------------|------|
| • Type of adhesive | Silane modified polymer | • Holding power of strip up to | 5 Kg |
|--------------------|-------------------------|--------------------------------|------|

# tesa® Adhesive Screw Triangular for Brick & Stone 5kg

## Product Information

### Properties/Performance Values

|                                |                         |                             |     |
|--------------------------------|-------------------------|-----------------------------|-----|
| • Application temperature from | 5 °C                    | • Ozone resistance          | yes |
| • Chemical Resistance          | yes                     | • Residue-free removability | yes |
| • Hazard material              | no                      | • Reusable                  | no  |
| • Humidity resistance          | yes                     | • UV resistant              | yes |
| • Material                     | Copper, Stainless steel | • Waterproof                | yes |
| • Oil and grease resistance    | no                      |                             |     |

## Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?cp=77904>