



# TRANSFER TAPE FOR LIGHTWEIGHT MOUNTING APPLICATIONS

The Tackified Acrylic Transfer Tape tesa® 75507 Offers a Range of Benefits

- Suitable for a wide range of applications due to its very good initial adhesion to a wide variety of surfaces
- **High durability** as it is temperature, humidity and ageing resistant
- Equipped with our proven and well-known tesa® 4965 adhesive





# DURABLE AND CONFORMABLE FOR ALL KINDS OF MOUNTING AND LAMINATION WORK

#### Application areas:

- Mounting of lightweight parts and materials
- Mounting of foams, felts, fabrics and textiles
- Mounting of flooring systems
- Membrane switch mounting
- Lamination of insulation materials
- Splicing

## Product features:

- Transfer tape design makes it highly conformable and suitable for a wide range of applications
- Very good initial adhesion to a wide variety of materials
- High durablitity due to its very good temperature and humidity resistance
- Good die cutting properties

### References for applications



Leightweight mounting



Foam lamination



Fabric and textile mounting

#### Technical data

| Product            | Backing | Type of<br>adhesive  | Color       | Type of liner | Total<br>thickness<br>[µm] | Thickness<br>of liner<br>[µm] | Adhesion to<br>steel<br>[N/cm] | Dimensions<br>(m:mm) |
|--------------------|---------|----------------------|-------------|---------------|----------------------------|-------------------------------|--------------------------------|----------------------|
| tesa® <b>75507</b> | None    | Tackified<br>acrylic | Transparent | Glassine      | 75                         | 70                            | 11.0                           | 300 : 1372           |

tesa SE Phone: +49 40 88899 0 tesa.com/company/locations

tesa.com

04/202C

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All technical information and data above mentioned are provided to the best of our knowledge on the basis of our practical experience. They shall be considered as average values and are not appropriate for a specification. Therefore tesa® SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. The user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.