



Dear customer, please check this proof carefully and confirm your print approval in writing with your signature and date. Your approval for this proof includes size, position, correctness and colour of all printed elements, plus the information in the legend and is required for the further processing of your job. After your approval we will transfer the artwork files according to this proof for subsequent prepress steps. Should this proof contain mistakes, which have not been objected by you, be informed, that we have to reject any claims for indemnification after the approval.

# DIE BESTEN VERPACKUNGSLÖSUNGEN



**WORAUF KOMMT ES IHNEN AN?**

	PVC-Träger			Nachhaltige Alternativen		PP-Träger			Nachhaltige Alternativen		Spezial	
	tesapack® ULTRA STRONG	NOPI PVC	tesapack® 4120	tesapack® PAPER	tesapack® BIO & STRONG	tesa® 4195	NOPI Classic	NOPI Universal	tesapack® PAPER STANDARD	tesapack® ECO & STRONG	tesapack® EXPRESS PP	tesapack® ULTRA RESISTANT
<b>Produktnummer</b>	51124, 57174, 57175, 57176, 57177	57214, 57215	04120	05054, 55337, 57180	58296	04195	57209, 57210, 57211, 57212	57950, 57951, 57952, 57953, 57457, 57458	58291, 58292, 58293	58153, 58154, 58155, 58156	57804, 57810	45900, 45902
<b>Max. Kartongewicht*</b>	< 30 KG 	< 20 KG 	< 15 KG 	< 20 KG 	< 20 KG 	< 30 KG 	< 20 KG 	< 15 KG 	< 10 KG 	< 15 KG 	< 15 KG 	< 50 KG 
<b>Gesamtdicke</b>	65 µm	65 µm	49 µm	107 µm	50 µm	60 µm	50 µm	45 µm	125 µm	54 µm	60 µm	105 µm
<b>Klebkraft</b>	■■■	■■■	■■■	■■■	■■■	■■■	■■■	■■■	■■■	■■■	■■■	■■■
<b>Reißfestigkeit</b>	■■■	■■■	■■■	■■■	■■■	■■■	■■■	■■■	■■■	■■■	■■■	■■■
<b>Hohe Anfangsklebkraft für sofortigen Verschluss</b>	■■■	■■■	■■■	■■■	■■■	■■■	■■■	■■■	■■■	■■■	■■■	■■■
<b>Leise abrollbar</b>	●	●	●			●	●	●	●		●	
<b>Verletzungsbeständig</b>	●	●	●							●		●
<b>Zur Lagerung im Kühlhaus geeignet</b>	●	●	●		●				●			
<b>UV- und altersbeständig</b>						●	●	●		●	●	
<b>Für Gefahrgüter geeignet</b>	●					●						●
<b>Von Hand einreißbar</b>				●					●		●	
<b>Empfohlen für</b>	←  →			←  →			←  →		←  →			

\* Empfehlungen für das Gewicht von Kartons vorbehaltlich Kartonqualität, Transportbedingungen (kein extremes Herunterfallen des Kartons), Befüllung (kein Überfüllen), Transport und Lagertemperatur (nicht über 40 °C).