



tesamoll® D-Profile

Product Information

BNR 05389, 05393, 55706

Product Description

The tesamoll® D-Profile is a long-lasting rubber seal for doors and windows. It is an effective door & window draught stopper and able to seal even wider gaps.

Product Features

- Saves up to 40% of energy costs
- Self-adhesive, long-lasting rubber D-Profile
- Seals all gaps from 3 to 7mm
- Durability: 8 years
- Weather-, UV- and ozone-resistant
- Wipe-clean
- Easy to apply and to fit without screws or nails
- Easy to remove
- Temperature-resistant from -50°C to +60°C

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|--------------------|------------------|---------------------------------|------|
| • Backing | EPDM rubber foam | • Energy saving potential up to | 40 % |
| • Type of adhesive | synthetic rubber | • Gap coverage up to | 7 mm |

Properties/Performance Values

- | | | | |
|-----------------------------|-------------------|-------------------------------|--------|
| • Chemical Resistance | no | • Solvent free | yes |
| • Durability | 8 years | • Temperature resistance | yes |
| • Humidity resistance | yes | • Temperature resistance max. | 60 °C |
| • Material | Fabric, Synthetic | • Temperature resistance min. | -20 °C |
| • Residue-free removability | no | | |



tesamoll[®] D-Profile

Product Information

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?cp=NaN>