

tesa® Powerstrips Self-Adhesive Picture Hook

Product Information

BNR 58031, 64359

Product Description

Self-adhesive and removable tesa Powerstrips Picture Hooks are the smart alternative to hang up a picture without the need to drill holes and damage the wall.

Product Features

- Easy to mount without drilling, screws or nails
- Holds objects of up to 1 kg*
- Removable without a trace thanks to the Powerstrips® technology
- Alternative solution to nails and screws
- Hook reusable with tesa Powerstrips LARGE

*Not suitable for use on styrofoam, foamed material, surfaces with non-stick coating, porous materials

Application Fields

- How to use - Step by step
1. Clean the surface with alcohol or silicone-free glass cleaner
 2. Apply the Powerstrip Large strip on the surface - press for 5 seconds minimum
 3. Stick the hook onto the strip - press for 5 seconds minimum
 4. Make sure the tab can be accessed for removal

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|-----------------------|------------------|-----------------|-------------|
| • Type of adhesive | synthetic rubber | • Hook shape | Rectangular |
| • Holding power up to | 1 Kg | • Silicone free | yes |

Properties/Performance Values

- | | | | |
|--------------------------------|---|-----------------------------|-----|
| • Application temperature from | -15 °C | • Ozone resistance | yes |
| • Applicationfield | Kitchen, Living room,
Children's room,
Office, Hall, Bathroom | • Residue-free removability | yes |
| • Chemical Resistance | no | • Reusable | yes |
| • Hazard material | no | • Solvent free | yes |
| • Humidity resistance | no | • Temperature resistance | yes |
| • Material | PS (polystyrene) | • UV resistant | no |
| • Oil and grease resistance | no | • Waterproof | no |

tesa® Powerstrips Self-Adhesive Picture Hook

Product Information

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?cp=58031>