

# tesa® 4206



## Product Information

Highly transparent adhesive film

tesa® 4206 is based on a highly transparent PP-film backing and is coated with an extremely non-aging and light-resisting adhesive.

tesa® 4206 is characterised by smooth and low noise unwinding features.

### Main Application

tesa® 4206 is universally used for:

- packaging applications where high transparency and very good aging stability are needed
- mounting of litho films
- label protection on chemical bottles
- splicing of film (photo-printing)

### Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

#### Technical Data

• Backing material	PP film	• Elongation at break	150 %
• Total thickness	58 µm	• Tensile strength	43 N/cm
• Type of adhesive	acrylic		

#### Adhesion to

- |         |          |
|---------|----------|
| • steel | 3.4 N/cm |
|---------|----------|

### Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit  
<http://l.tesa.com/?ip=04206>