




tesa® 51136 PV0



Product Information

Overmasking and surface protection film for the protection of various surfaces mainly in the automotive interior

Product Description

tesa® 51136 PV0 is a 105 µm self-adhesive polyethylene tape with an acrylic adhesive for masking large areas of plastic parts during professional automotive painting processes. The color of the tape provides a good contrast to dark surfaces making positioning easier and faster.

Furthermore, tesa® 51136 PV0 is an interior surface protection tape for slightly structured surfaces. It is a higher adhesion version for rough surfaces and carpets.

Product Features

- Green translucent film
- Good adhesion and traceless removal
- Versatile with regards to use on surfaces like PP, ABS, and textile
- Cost saving due to reduction in rectification and final repair
- No special equipment needed, ensuring simple, low cost application and removal processes
- Easy disposal. Both film and adhesive system are environmentally friendly

Application Fields

tesa® 51136 PV0 is used for masking large areas of plastic parts during professional automotive painting processes and for the protection of various surfaces in automotive interiors made of plastic or textiles against dirt and damage during storage, assembly, and transportation.

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|--------------------|---------|-------------------|--------|
| • Backing material | PE film | • Total thickness | 105 µm |
| • Type of adhesive | acrylic | | |

Properties/Performance Values

- | | | | |
|--------------------|---------|------------------|-----|
| • Tensile strength | 19 N/cm | • Easy to remove | yes |
|--------------------|---------|------------------|-----|

Adhesion to Values

- | | |
|---------|----------|
| • Steel | 2.4 N/cm |
|---------|----------|



tesa[®] 51136 PV0

Product Information

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=51136>