

tesa[®] 7140 Roll Masker



Product Information

Efficient overmasking solution for automotive two-tone painting at high temperatures

Product Description

tesa[®] 7140 RollMasker is a combination of tesa[®] 7140 fineline tape and tesa[®] high temperature film for large area masking during two-tone car painting in the paint shop at automotive OEMs.

The combination of tape and film reduces process times and material waste at the OEM compared to a stand-alone filmic hood.

Standardized and customized applicators for tesa[®] 7140 RollMasker are available to ensure efficient tape application.

Product Features

- Highly temperature resistant material up to 170°C
- High tear resistant tape to avoid tearing during demasking
- Risk of overspray and paint deformation are eliminated through static film loading
- It ensures efficient and reliable masking application with a maximum temperature resistance of up to 170°C/1h, thus allowing dry demasking processes.

Application Fields

tesa[®] 7140 RollMasker is suitable for high temperature two-tone car body masking.

Example applications are:

- * Two-tone car body painting
- * Two-tone inline masking
- * Masking with dry demasking processes
- * Large area masking at high drying temperatures
- * Efficient overmasking

For latest information on this product please visit <http://l.tesa.com/?ip=7140RMHT4380>

tesa[®] 7140

Roll Masker

Product Information

Application Fields

To ensure the highest performance possible, our aim is to fully understand your application (including the substrates involved) in order to provide the right product recommendation.

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|--------------------|----------------|-------------------|--------|
| • Backing material | PVC film | • Total thickness | 168 µm |
| • Type of adhesive | natural rubber | | |

Properties/Performance Values

- | | | | |
|--------------------------------|---------|-----------------------------------|--------|
| • Tensile strength | 73 N/cm | • Sharp color edge | yes |
| • Easy to remove | yes | • Temperature resistance (30 min) | 170 °C |
| • Material of masking coverage | HDPE | • Thickness of masking coverage | 30 µm |
| • Paint anchorage | yes | | |

Adhesion to Values

- | | |
|---------|--------|
| • Steel | 4 N/cm |
|---------|--------|

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=7140RMHT4380>