

# tesa® extra Power 56064

Silicone

## **Product Information**

### Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Total thickness

500 μm

#### **Product Construction**

· Backing material

Properties/Performance Values			
<ul><li>Tensile strength</li><li>Adhesive strength</li></ul>	33 N/cm Very high adhesion	<ul><li>Ozone resistance</li><li>Residue free removal</li></ul>	yes yes
<ul><li>Ageing resistance (UV)</li><li>Application temperature from</li><li>Application temperature to</li></ul>	yes -60 °C +260 °C	<ul><li>Reusable</li><li>Solvent free</li><li>Spare part service</li></ul>	no yes no
<ul><li>Applicationfield</li><li>Area of use</li></ul>	Home, Garden, Car, Garage Outdoor	Suitable surfaces	Even wood, Tiles, Brick, Most plastics, Glass, Acrylic glass,
<ul><li>Batteries included</li><li>Batteries required</li></ul>	no no		Plaster, Metal, Steel, Stone
<ul><li>Ecofriendly packaging</li><li>Hand tearability</li></ul>	no no	Tear resistance Temperature resistance	yes yes
<ul><li>Hazard material</li><li>Humidity resistance</li><li>Material</li></ul>	no yes Silicone	<ul><li>Temperature resistance max.</li><li>Temperature resistance min.</li><li>Tensibility</li></ul>	260 °C -60 °C 750 %
Oil and grease resistance	yes	<ul><li>UV resistant</li><li>Water resistance</li></ul>	yes yes
		<ul><li>Waterproof</li><li>Writable</li></ul>	yes no



# tesa® extra Power 56064

**Product Information** 

### Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.

