



tesa® Powerstrips 57519

Product Information

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|-----------------------|------------------|-----------------|------|
| • Type of adhesive | synthetic rubber | • Hook shape | Oval |
| • Holding power up to | 1 Kg | • Silicone free | yes |

Properties/Performance Values

- | | | | |
|--------------------------------|-------------------|-------------------------------|---|
| • Application temperature from | 15 °C | • Ozone resistance | no |
| • Application temperature to | 35 °C | • Residue free removal | yes |
| • Applicationfield | Bathroom, Kitchen | • Reusable | yes |
| • Area of use | Indoor | • Reusable with | Powerstrips Small |
| • Batteries included | no | • Solvent free | yes |
| • Batteries required | no | • Suitable surfaces | Glazed Tiles, Glass,
Even wood, Steel,
Acrylic glass, Most
plastics, Metal |
| • Chemical resistance | no | | |
| • Hazard material | no | | |
| • Humidity resistance | no | | |
| • Humidity sealing | no | • Temperature resistance | yes |
| • Material | PS (polystyrene) | • Temperature resistance max. | 35 °C |
| • Number of hooks | Single | • Temperature resistance min. | 15 °C |
| • Oil and grease resistance | no | • UV resistant | no |
| | | • Water resistance | no |
| | | • Waterproof | no |

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=57519>