



# tesa® Softprint 52062 BigFoam LT



## Product Information

Foam plate mounting tape for flexographic printing

## Product Description

tesa® 52062 Softprint BigFoam LT is a 1500µm double-coated foam tape designed specifically for mounting photopolymer plates in wide-web film and paper flexographic printing.

Due to its medium hardness foam it is particularly suited for high quality combination of half-tone and solid work.

## Product Features

- tesa® Softprint BigFoam LT is highly compressible and therefore offers improved print quality and higher running speeds
- tesa® Softprint's BigFoam LT unique construction ensures that print quality is maintained even on extended print run
- The special low tack adhesive on the plate side ensures very simple mounting, very easy repositioning, and demounting of plate and tape without residues
- During printing a very good bond of tape and plate is achieved - no edge lifting and no plate movement
- The structured PP-liner prevents the formation of air pockets when plate mounting

## Application Fields

tesa® 52062 Softprint BigFoam LT is a 1500µm (60 mil) category double-coated foam tape, designed specifically for mounting photopolymer plates in wide-web film and paper flexographic printing.

## Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

## Product Construction

- |                    |                   |                 |    |
|--------------------|-------------------|-----------------|----|
| • Backing material | PE foam           | • Type of liner | PP |
| • Type of adhesive | tackified acrylic |                 |    |

## Properties/Performance Values

- |            |        |                      |      |
|------------|--------|----------------------|------|
| • Hardness | medium | • Thickness category | 1500 |
|------------|--------|----------------------|------|



# tesa® Softprint 52062 BigFoam LT

Product Information

## Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=52062>