



tesa® EasySplice 51788 Black Plus



Product Information

Multifunctional splicing tape with integrated optical detection feature

Product Description

tesa® 51788 EasySplice Black Plus is a double-sided integrated flying splice tape consisting of a flat-back paper and an acrylic adhesive.

Colour: Black

Product Features

- Very high tack properties
- Very high shear resistance
- Extremely good heat resistance
- Best adhesion on coated and uncoated paper
- Smooth and easy application due to a flexible backing
- Low splice thickness
- Reliable detection of splice position
- Slit liner for the secure fixation of the top sheet is included
- Adhesive formulation with very high tack properties for excellent contact between expiring web and new reel
- One splitting strip with paper backing for a smooth opening of the new paper reel without jeopardising the printing process
- Black backing for a reliable optical detection of the splice position

Application Fields

tesa® 51788 EasySplice Black Plus is particularly suitable for:

- Flying splices in web printing industry

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|--------------------|------------|---------|-------|
| • Backing material | flat paper | • Color | black |
| • Total thickness | 110 µm | | |

Properties/Performance Values

- | | | | |
|-----------------------|---------|-----------------------------------|-----------|
| • Elongation at break | 7 % | • Shelf life time (packed) < 25°C | 18 months |
| • Tensile strength | 29 N/cm | | |

For latest information on this product please visit <http://l.tesa.com/?ip=51788>



tesa® EasySplice 51788 Black Plus

Product Information

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.

For latest information on this product please visit <http://l.tesa.com/?ip=51788>