

tesa® Softprint 72724 Secure-X

Product Information

Foam plate mounting tape: CLASSIC Product Design

Product Description

Double-sided foam tape

Product Features

- Foam properties: Low thickness tolerance. Long lasting, constant recovery characteristics
- Adhesive properties: Low tack surface characteristics. Sufficient plate demounting. Excellent tape bonding towards sleeve side. Excellent plate bonding
- Structured PP-liner to prevent formation of air pockets when the plate is mounted

Application Fields

Mounting of 1,14 mm (0,045") and 1,70 mm (0,067") flexographic printing plates onto steel /alu /PU and glassine cylinders

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

•	Backing material	PE foam with film	•	Type of liner	PP
		lamination	•	Total thickness	550 μm

• Type of adhesive tackified acrylic

Properties/Performance Values

•	Color of logo	purple	•	Thickness category	500
	Hardness	medium			





tesa® Softprint 72724 Secure-X

Product Information

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.

