



tesa® 64014

Product Information



Low noise packing tape - available in clear & brown

Product Description

tesa® 64014 is based on a PP-backing coated with a water based acrylic adhesive.

Product Features

- The special material combination guarantees a low noise unwinding behaviour.
- Water based acrylic adhesive
- tesa® 64014 has a high age and light resistance.
- The product is chlorine free and based on derivatives of mineral oil only
- The disposal by heat treatment is environmental friendly.

Application Fields

- Packaging, bundling and closing * Sealing of light and medium-range weight cartons

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|--------------------|---------|-------------------|-------|
| • Backing material | PP film | • Total thickness | 45 µm |
| • Type of adhesive | acrylic | | |

Properties/Performance Values

- | | | | |
|-----------------------|---------|----------------------|-----|
| • Elongation at break | 140 % | • Manual application | yes |
| • Tensile strength | 35 N/cm | | |

Adhesion to Values

- | | |
|---------|----------|
| • Steel | 2.4 N/cm |
|---------|----------|



tesa® 64014

Product Information

Additional Information

tesa® 64014 can be applied on all manual dispenser. For a more convenient application it is recommended to loose the dispenser friction. The PV1-version of the product is printable. Available colours: white, havana and transparent

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=64014>