

tesa® On & Off 55228

Product Information

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

 Backir 	g material	polyamid	 Type of adhesive 	synthetic rubber
----------------------------	------------	----------	--------------------------------------	------------------

Properties/Performance Values

 Adhesive strength 	Very high adhesion	• Open & Closable up to	1000 time(s)
 Applicationfield 	Home, Office, Car,	 Residue free removal 	no
	Garage	 Reusable 	no
 Area of use 	Indoor	 Solvent free 	yes
 Batteries included 	no	 Spare part service 	no
 Batteries required 	no	 Suitable surfaces 	Even wood, Tiles,
 Hand tearability 	no		Most plastics, Metal,
 Material 	Polyamid		Steel
		 UV resistant 	no

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.

