

tesa® 4287

Product Information



Tensilized Strapping Tape

Product Description

tesa® 4287 is a tensilized polypropylene strapping tape with a natural rubber adhesive system. The MOPP-film backing makes tesa® 4287 conformable.

Product Features

- tesa® 4287 exhibits good tensile strength with low elongation at the same time.
- The natural rubber adhesive offers excellent tack, as well as excellent adhesion to polar and non-polar substrates.
- The strapping tape features a very short dwell time until reaching its final adhesive strength.
- After use, the tape offers a residue-free removal and will leave no discoloration.

Application Fields

- tesa® 4287 is used in a variety of industrial applications: palletizing, belting of electronic components, bundling and closure of shipping cartons
- The strapping tape offers good temperature-resistance
- tesa® 4287 features residue-free removal

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|--------------------|------------------|-------------------|--------|
| • Backing material | MOPP | • Total thickness | 80 µm |
| • Type of adhesive | synthetic rubber | • Color | orange |

Product Assortment

- | | |
|--------------------|---------------------|
| • Available colors | transparent, orange |
|--------------------|---------------------|

Properties/Performance Values

- | | | | |
|-----------------------|----------|---------------------|-----|
| • Elongation at break | 35 % | • No discolouration | yes |
| • Tensile strength | 190 N/cm | | |

Adhesion to Values

- | | |
|---------|--------|
| • Steel | 6 N/cm |
|---------|--------|

tesa® 4287

Product Information

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=4287EU>