

# tesa® 60416

## Product Information



### Sustainable Aspects



For more information: <https://www.tesa.com/product-sustainability>

### Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

### Product Construction

• Backing material	PET film	• Total Sustainable Product Content	Post-consumer recycled content of liner
• Post-consumer recycled content of backing	90 %		
• Type of adhesive	acrylic	• Total thickness	42 µm

### Product Assortment

• Available colors	transparent, white, brown
--------------------	---------------------------

### Properties/Performance Values

• Elongation at break	100 %	• Printability	yes
• Tensile strength	45 N/cm	• Silent unwinding	yes
• Hand tearability	no	• Suitable for deep freezing	yes
• Humidity resistance	yes	• Transport Information	Temperature 0-70°C
• Packaging Weight	Up to 30 kg		

### Adhesion to Values

• Steel	3 N/cm
---------	--------

### Certificates

#### Sustainability Certificates

- Adhesive removability in the recycling process tested according to INGEDE method 12 at an independant institute.

# tesa® 60416

## Product Information

### Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=60416>